



| PRODUCT CODES | | |
|---------------|---------|----------|
| 3/4" | 7 1/16" | WC118-7G |
| 5/8" | 7 1/16" | WC118-7S |

| SPECIFICATIONS | |
|-------------------|-------------------------------------|
| COLOR/SHADE | BROWN/LIGHT |
| CONSTRUCTION | ENGINEERED FLOORING |
| WEAR LAYER | (3/4") 5.5mm OR (5/8") 4mm |
| PLYWOOD | 100% BALTIC BIRCH MULTIPLEX PLYWOOD |
| FINISH | UNFINISHED |
| PATTERN | 1-STRIP/PLANK |
| JANKA/HARDNESS | 1360 |
| SPECIES | EUROPEAN OAK 3/4" |
| THICKNESS | OR 5/8" |
| WIDTH | 7 1/16" |
| LENGTH | NOMINAL 2ft - 10ft |
| MOISTURE CONTENT | 8 - 12% |
| COLLECTION | HARGROVE |
| ORIGIN | WESTERN EUROPE |
| KNOT CONTENT | LIMITED SMALL KNOTS |
| HOLE CONTENT | FILLED |
| HEARTWOOD CONTENT | 95% OR BETTER |
| CHECKING | NONE |
| GRAIN | MIXED |
| GRADING | SELECT (PRIME) |
| LEED CREDITS | _____ |

GILFORD PLANK DESCRIPTION

Beautiful Unfinished European Oak Engineered Flooring.

Pre-Sanded, with a final toplayer thickness around either 6mm or 4mm depending on overall thickness, and only very occasional very small (up to 10-12mm) tight knots allowed. This is a unique beauty creating versatility to match a variety of colors in any location. Lengths from 6ft to 10ft (with occasional cut backs to 2ft allowed.)

It is as close to a solid wood as you can get with the benefits of engineered stability.

Widths available Include

130MM - 5.11" , 160MM - 6.29" , 180MM - 7.07" , 220MM- 8.66" , 240MM - 9.45" , 260MM - 10.24" , 300MM - 11.81"

OPTIONS & UPGRADES

- Beveled Edged or Squared edge options
- Custom Widths and lengths—Available upon request

WORLDWIDE SOURCE FOR WOOD

1210 ARION PARKWAY SAN ANTONIO TX 78216 | 210.298.9663 | WWW.WOODCO.COM | INFO@WOODCO.COM